

ASSEMBLY & INSTALLATION NOTES

JUBU aluminum alternator pulley (JU00005PRD)

for 2GR-FE

Please follow the instructions in this manual for a proper assembly & installation of the JUBU aluminum alternator pulley 2GR-FE.

Please find in this document:

- 1. PART LIST**
- 2. ASSEMBLY & INSTALLATION NOTES**


1. PART LIST for product JU0005PRD

#	ITEM	ART-NO.	UNITS
1	JUBU aluminum alternator pulley 7PK	JU00114ART	1
2	Nut DIN6923 M14x1.5	JU00259ART	1



Fig 1: Scope of delivery

2. ASSEMBLY & INSTALLATION NOTES

1. Uninstall the OEM belt pulley at the alternator
2. The aluminum alternator pulley (1) is bolted onto the alternator with the M14x1.5 nut (2) which is tightened with 110Nm and fixed with *LOCTITE 243* screw locking lacquer.
3.  **NOTE: For the final suit of screwing a special tool is required to fix the alternator (rotating) . Alternatively this step can also be done with an impact wrench.**

If you have any questions or need additional information, please contact us by email:

info@jubu-performance.com

JUBU Performance GmbH

Saxenegg 3a, 4323 Münzbach, AUSTRIA