

ASSEMBLY & INSTALLATION NOTES

JUBU titanium wheel bolts (JU00208PRD)

for Exige S3, 311, Evora and Emira

Please follow the instructions in this manual for a proper assembly & installation of the JUBU titanium wheel bolts for Exige S3, 311, Evora and Emira.

Please find in this document:

- 1. PART LIST
- 2. ASSEMBLY & INSTALLATION NOTES

1. PART LIST for product JU00208PRD

#	ITEM	ART-NO.	UNITS	
1	Titanium wheel bolt	JU00730ART	20	



Fig 1: Scope of delivery

 $\textbf{FILE:} \ \ \mathsf{UBU_titanium_wheel_bolts_Exige-S3-Evora-Emira_24-04-2024}$

REL_DATE: 11.07.2024 VERSION: 1.0



2. ASSEMBLY & INSTALLATION NOTES

1. On the first few threads of the titanium bolt (1) dry lubricant or anti-seize lubricant is applied. This can be skipped if some of the lubricant is left from the previous mounting.

ATTENTION! Use only dry lubricant or anti seize lubricant! Economical use is preferred! Use no oil or standard grease!

2. Fasten the titanium wheel bolts with 110Nm to 120Nm.



A NOTE: Check the torque after the first drive.

If you have any questions or need additional information, please contact us by email: info@jubu-performance.com

> JUBU Performance GmbH Saxenegg 3a, 4323 Münzbach, AUSTRIA

FILE: UBU_titanium_wheel_bolts_Exige-S3-Evora-Emira_24-04-2024

REL_DATE: 11.07.2024 VERSION: 1.0